

www.weitzer-parkett.com



## Weitzer Block 750 F Plus



### 2-layer engineered parquet

Dimensions: 750 x 125 x 10,3mm

### Installation methods:

### Functionalities:



**MAINTENANCE-FREE PARQUET:** For residential use the complicated and time-consuming maintenance is no longer required




**HEALTHY PARQUET:** Comfortable room climate. Allergy-friendly, Antibacterial, breathable and antistatic properties



**SOUND-REDUCTION PARQUET:** ambient noise drastically reduced at full adhesion

### Laying patterns:



### Product description:

Place of production	Austria
Total thickness	10,3mm. 2-layer construction
Wear layer	approx. 3,6mm solid wood
Supporting material	wood with vertically arranged growth rings
Profiling	4-side tongue and groove. 1-strip
Moisture content	long seasoned and kiln-dried wood (moisture content at delivery 8% ± 1%)
Under-floor heating	suitable (refer to Technical Datasheet MB020)
Fire resistance EN 13501-1	D <sub>fl</sub> -s1 with Pro Active+ or Pro Vital f surfaces (please pay attention to the conditions for installation)
Heat conductivity resistance	0,073 m <sup>2</sup> K/W
Renovation	multiple sanding possible
Hardness	23-42 N/mm <sup>2</sup> (depending on the type of wood)
Ecological responsibility	



### Surfaces:



#### PROACTIVE+ – THE NATURAL MATT SURFACE

Maintenance-free for private living areas. Matt lacquered surface with the look of a natural oiled surface. Antistatic and with antibacterial properties. Corresponds to stress class C according to ÖNORM C 2354 for particularly heavy use in terms of scratch resistance and chemical resistance. Meets standard requirements according to EN 425 in chair roll test. Slip resistance class R 10 acc. to DIN 51130.



#### PROVITAL finish – THE NATURAL OILED SURFACE

Pure natural oils that penetrate deep into the pores, giving the parquet a special protection. Particularly breathable. Repairable as a whole or on single spots. Factory-finished oiled surface for private living areas (finish) - for use in public areas additional finish application after installation is mandatory. Natural coating material in accordance with ÖNORM C 2380. Slip resistance class R 10 according to DIN 51130.

### Intelligent characteristics:

- Multiple design possibilities incl. herringbone (90°) and French herringbone\*\* (45° and 60°)
- Wooden stairs WP MULTI – Parquet and stairs from a single source ensure the best possible color uniformity

### Concluding remarks:

Dimensional data and technical characteristics of wood may be subject to minor deviations due to material or production technology. PEFC/FSC on request. Any change to the product after delivery can lead to changes in the declared product properties (e.g. fire behavior or slide properties) and the contractor is not liable for this. Change in R-value possible depending on haptic characteristics, care films and cleaning residues. \*\* For the French herringbone version: total bar length approx. 9mm shorter - only suitable for full adhesion. Latest technical state 1-2024.